



## Alternate Catalog No. HF9-R Catalog No. 1SAT144000R1011

**Description:** HF9-R Electronic Compact Starter 24 VDC

**UPC No** 4013614515637

**Home > Starters > Electronic Starters**

The HF-R-range is used for forward and reverse running motors, as well as for switching non resistive loads. Without overload protection and setting range it is the most simple solution, which is as compact as the whole range. The control supply voltage is 24 V DC. For the control and main connection points ABB offers screw connections.

### Descriptors

|          |                     |
|----------|---------------------|
| Category | Electronic Starters |
|----------|---------------------|

### Specifications

|  |  |
|--|--|
| Function                                   | Reversed-on-line-starter   |
| Horsepower Rating UL/CSA                   | Nominal Switching Performance Full Load (power factor = 0.4) 3 hp<br>Nominal Switching Performance Full Load (power factor = 0.8) 6.1 hp |
| Full Load Amps Motor Use                   | 6.5 A  |
| Ambient Air Temperature                    | Operation -25 ... +70 °C<br>Operation Compensated -40 ... + 80 °C  |
| RoHS Status                                | Following EU Directive 2011/65/EU  |
| Maximum Operating Voltage UL/CSA           | Main Circuit 500 V AC  |
| Ampere Rating UL/CSA                       | 6.5 A  |
| Connecting Capacity Main Circuit UL/CSA    | Flexible with Ferrule 1x 24 ... 14 AWG<br>Flexible 1x 24 ... 14 AWG<br>Solid 1x 24 ... 14 AWG  |
| Connecting Capacity Control Circuit UL/CSA | Flexible with Ferrule 1x 24 ... 14 AWG<br>Flexible 16-8 AWG<br>Solid 1x 24 ... 14 AWG  |
| Tightening Torque UL/CSA                   | Control Circuit 5 ... 7 in-lb<br>Main Circuit 5 ... 7 in-lb  |
| Standards                                  | IEC/EN 60947-1<br>IEC/EN 60947-4-2<br>UL 60947-1<br>UL 60947-4-2   |
| Rated Operational Voltage                  | Main Circuit 500 V AC  |
| Operational Voltage                        | Maximum 550 V AC<br>Minimum 42 V AC  |
| Rated Frequency                            | Main Circuit 50Hz<br>Main Circuit 60 Hz  |
| Rated Control Supply Voltage               | 24 V DC  |
| Rated Input Voltage                        | Switching Threshold at Signal 0 > -3 ... 9.6 V<br>Switching Threshold at Signal 1 > 19.2 ... 30 V  |
| Rated Impulse Withstand Voltage            | Main Circuit 6 kV  |
| Rated Insulation Voltage                   | 500 V  |
| Rated Operational Current AC-51            | 9 A  |
| Rated Operational Current AC-53a           | 6.5 A  |
| Rated Control Supply Current               | 0.04 A   |
| Rated Uninterrupted Current                | 9 A  |


**by ABB**

## Specifications

|                                     |   |
|-------------------------------------|---|
| Input Current                       | 0.00 A  |
| Switching Frequency                 | ≤ 2 Hz<br>120 starts/min<br>7200 starts/h   |
| Rated Operational Power AC-53a      | 3 kW  |
| Overvoltage Category                | III   |
| Overload Protection                 | No overload protection  |
| Trip Class                          | None  |
| Number of Poles                     | 3   |
| Power Loss                          | Maximum 14,6 W<br>Minimum 1,1 W   |
| Number of Protected Poles           | 3   |
| Mechanical Durability               | 10000 cycle   |
| Electrical Durability               | 30000000 cycle  |
| Delay Time                          | Off, Maximum, Switched Off via Supply Voltage 500 ms<br>Off, Typical, Switched Off via Control Input Voltage 30 ms<br>Off, Typical, Switched Off via Supply Voltage 25 ms<br>Off, Maximum, Switched Off with Pushbutton 3 second [unit of time]<br>Off, Minimum, Switched Off with Pushbutton 0.5 second [unit of time] |
| Mounting on DIN Rail                | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715  |
| Mounting Position                   | Position 1, load side bottom  |
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup><br>Flexible 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid 1x 0.5 ... 4 mm <sup>2</sup>   |
| Connecting Capacity Main Circuit    | Flexible with Ferrule 1x 2 ... 2.5 mm <sup>2</sup><br>Flexible 1x 2 ... 2.5 mm <sup>2</sup><br>Rigid 1x 2 ... 2.5 mm <sup>2</sup>   |
| Recommended Screw Driver            | Control Circuit M3<br>Main Circuit M3   |
| Terminal Type                       | Screw Terminals   |
| Tightening Torque                   | Control Circuit 0.5 ... 0.6 N·m<br>Main Circuit 0.5 ... 0.6 N·m   |
| Wire Stripping Length               | Control Circuit 8 mm<br>Main Circuit 8 mm   |
| Pollution Degree                    | 2   |
| Phase Loss Sensitive                | Yes   |
| Degree of Protection                | Housing IP20<br>Main Circuit Terminals IP20   |
| Short-Circuit Current Rating (SCCR) | (500 V AC, 30 A Class J or CC) 100 kA   |

## Classifications

|          |  |
|----------|--|
| ETIM 5.0 | EC001037 - Motor starter combination               |
| ETIM 6.0 | EC001037 - Motor starter/Motor starter combination |
| ETIM 7   | EC001037 - Motor starter/Motor starter combination |
| eClass   | 7.0 27370905                                       |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 22.5 mm  |
| Product Net Height         | 99 mm    |
| Product Net Depth / Length | 114.5 mm |
| Product Net Weight         | 0.174 kg |

**Package Information**

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 150 mm        |
| Package Level 1 Depth / Length | 115 mm        |
| Package Level 1 Height         | 34 mm         |
| Package Level 1 Gross Weight   | 0.274 kg      |
| Package Level 1 EAN            | 4013614515637 |

**Safety Information**

|                      |           |
|----------------------|-----------|
| Mean Time to Failure | 39.6 year |
|----------------------|-----------|