

Representative Image

## Catalog No. 9T14A1001G03

**Description: 3A,15KVA,480-208Y,150C,N2,K4,ES,DOE**

**UPC No 783173901939**

**Home > Transformers > Dry Type Vented > K-Factor**

ABB's K-Factor transformers are designed to withstand the additional heating that accompanies the presence of harmonics in electrical systems. K-Factor transformers are designed not to eliminate harmonics, but to withstand their negative effects. They are available with aluminum or copper windings and in all three temperature rise ratings. K-Factor transformers meet DOE 2016 efficiency standards and are UL Listed and Energy Verified. Qualified to the seismic requirements of IEEE-693-2005 and the IBC-2021 and CBC 2022.

### Descriptors

| | |
|---|---|
| Category | K-Factor |

### Specifications

| | |
|---|---|
| TransType | DOE 2016 |
| Phase | 3 |
| PriVoltage | 480 |
| SecVoltage | 208Y/120 |
| KVA | 15 KVA |
| Coil Material | AL |
| TempRise | 150 °C |
| Frequency | 60 Hz |
| AmbTemp | 40 °C |
| EnergyEfficiency | DOE 2016 |
| KFactor | K4 |
| Enclosure Type | NEMA 2 |
| Sound | Std |

### Classifications

| | |
|---|---|
| UL | Yes |