

## Catalog No. 9T83B4002G29

**Description:** 3A,27KVA,230-230Y/133,150C,N2,DIT

**UPC No** 783173214695

**Home > Transformers > Dry Type Vented > Drive Isolation**

ABB's 9T83 Drive Isolation Transformers (DIT) are designed to specifically handle the mechanical stresses, voltage distortions, and harmonics associated with silicon-controlled rectifiers (SCR) or Thyristor applications. Drive Isolation Transformers have symmetrically placed taps and added coil bracing to withstand the mechanical forces caused by severe SCR or thyristor duty cycles. These features also help to protect the transformer from the regenerative duty and more frequent momentary short-circuits associated with SCR commutation. The 9T83 DITs are UL Listed for installations outside of Canada. Qualified to the seismic requirements of IEEE-693-2005 and IBC-2021 and CBC 2022.



Representative Image

### Descriptors

Category	Drive Isolation
----------	-----------------

### Specifications

TransType	QL-TP1
Phase	3
PriVoltage	230
SecVoltage	230Y/133
KVA	27 KVA
Coil Material	AL
TempRise	150 °C
Sub Type	Drive Isolation (DIT)
Frequency	60 Hz
TempClass	220 °C
AmbTemp	40 °C
EnergyEfficiency	NEMA TP 1
KFactor	K1
Enclosure Type	NEMA 2
Sound	Std

### Classifications

UL	Yes
----	-----