



Representative Image

## Catalog No. THHQL32090

**Description: CIRCUIT BREAKER 3P 90A**

**UPC No 783164117776**

**Home > Circuit Breakers > Miniature Circuit Breakers > Q-Line Miniature Circuit Breakers**

Q line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications. The QL breakers are plug-in versions of the Q Line used for connection to load centers and lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers are available in 1, 2, and 3 pole versions, can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications. 2090 Amps 90 A

### Descriptors

|              |                                   |
|--------------|-----------------------------------|
| Category     | Q-Line Miniature Circuit Breakers |
| Product Line | Q-Line (Plug-In)                  |
| GO Schedule  | R8                                |

### Specifications

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Trip Style                      | Non-Interchangeable               |
| Frame Type                      | Q-Line                            |
| Amperage                        | 90 A                              |
| System Voltage                  | 120 Vac<br>120/240 Vac<br>240 Vac |
| Poles                           | 3                                 |
| Trip Function                   | LI                                |
| Continuous Current Rated        | Standard                          |
| 120 Vac Interrupting Rating     | 22 KAIC                           |
| 120/240 Vac Interrupting Rating | 22 KAIC                           |
| 240 Vac Interrupting Rating     | 22 KAIC                           |
| Suitable for Reverse Feed       | Yes                               |
| Wire Range (Cu/Al)              | 6-1/0 kcmil / 4-1/0 kcmil         |
| Long Time                       | Fixed                             |
| Instantaneous                   | Fixed                             |
| Protective Relays               | No                                |
| Current Metering                | No                                |
| Special Markings                | HACR                              |
| GSA Compliance                  | No                                |

### Classifications

|           |        |
|-----------|--------|
| UL File # | E11592 |
|-----------|--------|