

Representative Image

## Catalog No. TL42422C

**Description: MLO 225A 42CRT 3P4W 208Y/120V COMBO**

**UPC No 783164189957**

**Home > Load Center & Meter Combos > Load Centers**

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centrigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TL42422C features space for 42, 1" breakers, 3 phases, a 225 A bus ampere rating, and a combination/flush enclosure.

### Descriptors

| | |
|---|---|
| Category | Load Centers |
| GO Schedule | R7 |

### Specifications

| | |
|---|---|
| # Branch Circuit 250A | 42 |
| 1" Space | 42 |
| 1/2" Space | 0 |
| Amperage | 225 A |
| Circuit Breaker Style | Plug-In |
| Device type | Main Lug |
| Door | Yes |
| Enclosure | Indoor |
| Enclosure Type | Indoor, Combination |
| Factory Installed Ground Kit | No |
| Feed | Either |
| Input/Output Voltage | 208Y/120V ac |
| Interrupting Capacity Rating | 65 |
| Load Center Type | Standard |
| NEMA Rating | NEMA 1 |
| Phase | 3 Phase |
| Service & Voltage | 3 Phase, 4 Wire, 208Y/120V ac |
| Wires | 4 Wire |

### Classifications

| | |
|---|---|
| UL/CUL Listing | UL |

### Dimensions

| | |
|---|---|
| Height | 43.4 in |
| Weight | 41.2 lb |
| Width | 14.0 in |