



Representative Image

## Catalog No. TL42422C

**Description:** MLO 225A 42CRT 3P4W 208Y/120V COMBO

**UPC No** 783164189957

**Home > Load Centers > Load Centers**

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TL42422C features space for 42, 1" breakers, 3 phases, a 225 A bus ampere rating, and a combination/flush enclosure.

### Descriptors

Category	Load Centers
GO Schedule	R7

### Specifications

# Branch Circuit 250A	42
1" Space	42
1/2" Space	0
Amperage	225 A
Circuit Breaker Style	Plug-In
Device type	Main Lug
Door	Yes
Enclosure	Indoor
Enclosure Type	Indoor, Combination
Factory Installed Ground Kit	No
Feed	Either
Input/Output Voltage	208Y/120V ac
Interrupting Capacity Rating	65
Load Center Type	Standard
NEMA Rating	NEMA 1
Phase	3 Phase
Service & Voltage	3 Phase, 4 Wire, 208Y/120V ac
Wires	4 Wire

### Classifications

UL/CUL Listing	UL
----------------	----

### Dimensions

Height	43.4 in
Weight	41.2 lb
Width	14.0 in

**by ABB**

